



Челични Јажиња


Челични Јажиња за Лифтови

DIN 3063 - HRN C.H1.104

Примена: Лифтови
Конструкција: 8x19S+KJ,
8x19S+ČJ
Завршна изработка: црна-
замастена



8x19S+KJ



8x19S+ČJ

Шифра	Пречник јаже mm	Тежина kg/100m	Мин. прекидна сила(kN) Цврстина на жица(N/mm2)			
			1180/1770	1320/1620	1370/1570	1570/1770
19301	8	21.8	25.7	26.5	28.1	30.8
19302	9	27.5	32.5	—	35.6	38.9
19303	9.5	30.7	36.2	37.3	39.7	43.6
19304	10	34.0	40.1	41.3	44.0	48.1
19305	11	41.1	48.6	50.0	53.2	58.1
19306	12	49.0	57.8	59.5	63.3	69.2
19307	12.7	54.8	64.7	66.6	70.9	77.5
19308	13	57.5	67.8	69.8	74.3	81.2
19309	14	66.6	78.7	81.0	86.1	94.2
19310	14.3	69.5	82.1	—	—	98.3
19311	15	76.5	90.3	—	98.9	108
19312	16	87.0	103	106	113	123
19313	17.5	104	123	—	—	147
19314	18	110	130	134	142	156
19315	19	123	145	149	159	173
19316	20	136	161	165	176	192
19317	20.6	144	170	—	—	204
19318	22	165	194	200	213	233





Челични
Јажиња


Шифра	Пречник јаже mm	Тежина kg/100m	Мин. прекидна сила(kN) Цврстина на жица(N/mm2)		
			1180/1770	1370/1570	1570/1770
19331	8	26.0	33.6	35.8	38.0
19332	9	33.0	42.5	45.3	48.2
19333	9.5	36.7	47.4	50.4	53.7
19334	10	40.7	52.5	55.9	59.5
19335	11	49.2	63.5	67.6	79.1
19336	12	58.6	75.6	80.5	85.6
19337	12.7	65.6	84.7	90.1	95.9
19338	13	68.8	88.7	94.5	100
19339	14	79.8	102	110	117
19340	15	91.6	118	126	134
19341	16	104	137	143	152
19342	18	132	170	181	193
19343	19	147	190	202	215
19344	20	163	210	224	238
19345	22	197	254	271	288

DIN 3063 8x19S - HRN C.H1.104 8x19W - HRN C.H1.096


Примена: Лифтови
Конструкција: 8x19S+ČJ /
8x19W+ČJ / 8x25Fi+ČJ
Завршна изработка: црна-
замастена



8X19S+ČJ



8X19W+ČJ



8X25Fi+ČJ