







Челични Јажиња

Челични јажиња пластифицирани



| Шифра | Пречник (mm) | Тежина (kg/100m) | Мин.Прек.Сила(kN) 1770N/mm ² | |
|-------|--------------|------------------|--|---|
| 19501 | 1.5-2.5 | 1.27 | 1.32 |  6x7+KJ PVC/PP/PE |
| 19502 | 2.0-3.0 | 2.00 | 2.35 | |
| 19503 | 3.0-4.0 | 4.02 | 5.29 | |
| 19504 | 3.0-5.0 | 5.04 | 5.29 | |
| 19505 | 4.0-5.0 | 6.74 | 9.41 | |
| 19506 | 4.0-6.0 | 8.00 | 9.41 | |
| 19507 | 5.0-6.0 | 10.18 | 14.7 | |
| 19508 | 6.0-8.0 | 16.04 | 21.1 | |
| 19509 | 8.0-10 | 26.95 | 37.6 |  7x7 PVC/PP/PE |
| 19521 | 1.5-2.5 | 1.35 | 1.43 | |
| 19522 | 2.0-3.0 | 2.14 | 2.54 | |
| 19523 | 3.0-4.0 | 4.34 | 5.71 | |
| 19524 | 3.0-5.0 | 5.36 | 5.71 | |
| 19525 | 4.0-5.0 | 7.31 | 10.20 | |
| 19526 | 4.0-6.0 | 8.56 | 10.20 | |
| 19527 | 5.0-6.0 | 11.08 | 15.90 | |
| 19528 | 6.0-8.0 | 17.34 | 22.90 |  6x19+KJ PVC/PP/PE |
| 19529 | 8.0-10 | 29.25 | 40.60 | |
| 19541 | 3.0-4.0 | 3.91 | 4.90 | |
| 19542 | 3.0-5.0 | 4.93 | 4.90 | |
| 19543 | 4.0-5.0 | 6.56 | 8.70 | |
| 19544 | 4.0-6.0 | 7.82 | 8.70 | |
| 19545 | 5.0-6.0 | 9.90 | 13.60 | |
| 19546 | 6.0-8.0 | 15.64 | 19.60 | |
| 19547 | 8.0-10 | 26.24 | 34.80 |  7x19 PVC/PP/PE |
| 19548 | 10-12 | 39.60 | 54.40 | |
| 19549 | 12-14 | 55.74 | 78.30 | |
| 19561 | 3.0-4.0 | 4.23 | 5.29 | |
| 19562 | 3.0-5.0 | 5.25 | 5.29 | |
| 19563 | 4.0-5.0 | 7.12 | 9.40 | |
| 19564 | 4.0-6.0 | 8.38 | 9.40 | |
| 19565 | 5.0-6.0 | 10.78 | 14.70 | |
| 19566 | 6.0-8.0 | 16.90 | 21.20 |  6x12+7KJ PVC/PP/PE |
| 19567 | 8.0-10 | 28.48 | 37.60 | |
| 19568 | 10-12 | 43.10 | 58.80 | |
| 19569 | 12-14 | 60.80 | 84.60 | |
| 19571 | 2.0-3.0 | 1.57 | 1.48 | |
| 19572 | 3.0-4.0 | 3.06 | 3.33 | |
| 19573 | 3.0-5.0 | 4.08 | 3.33 | |
| 19574 | 4.0-5.0 | 5.04 | 5.92 | |
| 19575 | 4.0-6.0 | 6.29 | 5.92 | |
| 19576 | 6.0-8.0 | 12.22 | 13.30 | |
| 19577 | 8.0-10 | 20.20 | 23.70 | |

Не се за кревање товар!

Завршна Изработка: Поцинкувано + PVC/PP/PE PVC е безбојна пластика, одредена боја по нарачка
Дозволена работна температура е PVC-то 100°C.



Челични
Јажиња